

FEATURE PACKED TWO WAY RADIO

The GMRS-PRO is a premium GMRS radio, designed for those that need to get the most from their GMRS radio. The GMRS-PRO is backward compatible with all other GMRS and FRS radios.

If two or more users have a GMRS-PRO radio, several new options beyond just push-to-talk can be used. GMRS-PRO users can communicate with text messages, send GPS locations, request GPS locations, use SOS alerts, and more.

The GMRS-PRO is feature packed with bluetooth, GPS, on-board compass and more. It also includes a NOAA receiver and FM radio. The radio has the ability to easily scan and check for activity. The GMRS-PRO offers a fully IP67 water proof design for full protection from any elements.

FEATURES AND FUNCTIONS

- Bluetooth App Programmable
- Six Channel Banks
- Text and Location Sharing
- Onboard Compass
- Offline Maps and Location History
- Firmware Upgradeable
- GPS and Bluetooth
- IP67 Waterproof



TECHNICAL SPECIFICAT GENERAL	IONS	
Frequency Range	87-108MHz (FM Radio Only) 136-174MHz (RX Only) 400-520MHz (RX ONLY) GMRS Chnannel (RX/TX) Memory Channel:30	
Channels	6 Groups / 30 Channels (180 total)	
Antenna Impedance	50 ohm	
Operating Voltage	7.4V	
Frequency Stability	±2.5ppm	
Operating Temp.	-20°C ~ +60°C	
DIMENSIONS		
Dimensions	58 (W) X 125 (H) X 35 (D)mm	
Weight	Radio Body 150g / Battery 120g	
TRANSMITTER		
	WIDE BAND	NARROW BAND
Power Output	5W	
Modulation	16K0F3E	11K0F3E
Adjacent Channel Power	≥70dB	≥60dB
FM Noise	≥45dB	≥43dB
Spurious and Harmonic	≥60dB	≥60dB
Audio Response	±1~-3db(0.3~3khz)	±1~-3db(0.3~2.55khz)
Modulation Distortion	≤3%	
RECEIVER		
	WIDE BAND	NARROW BAND
Sensitivity (12dB SINAD)	≤0.20µV	≤0.22µV
Intermodulation	≥65dB	≥60dB
Adjacent Channel Selectivity	≥70dB	≥65dB
		+

≤70dB ±1~-3db(0.3~3khz)

≥45dB

≤3%

≤2W

False Signal Response

Signal to Noise Ratio

Modulation Distortion

Audio Power Output

Audio Response

≤70dB

±1~-3db(0.32.55khz)

≥40dB

